

DECLARATION

GERMAN CLEAN ACT - VDI GUIDELINE 2440 -

TA LUFT

PAGE 1 OF 1

Date: June 2016 Rev. 1

We hereby confirm that representative samples of

SC 1400

was verified by an accredited laboratory (Test Report No. 3028434) in a first-time test under the following conditions:

Initial gasket stress: 31.3 MPa
related to DN40/PN40: 31.1 MPa
Temperature of exposure: 150 °C
Period of exposure: 48 h.

Remaining gasket stress: 16.2 MPa
Test pressure (absolute): 1 bar
Period of leakage measurement: 24 h.

The leak rate measured with the Helium leak detector at the end of the period of the leakage measurement was :

1.1 · 10⁻⁶ mbar·l/(s·m)

Therefore the gasket is in compliance with the tightness criteria of VDI 2440. If the design of the sealing system can be expected to permit normal function in the long term in the given operating conditions and the characteristic sealing value as per DIN 28090-1 or EN 13555, respectively, are observed when choosing and dimensioning the flange connection, the gasket can be regarded as a high-grade sealing system for the purposes of TA-Luft.

Notes

It is the responsibility of the buyer to assure traceability of the material during any further downstream use up to and including the finished machined part as well as the equipment in which it is assembled.

Rev. 0 - Released in September 2015 Rev. 1 – Change in VDI norm

MN/June 2016



GUARNIFLON SPA

(Società Socio Unico soggetta all'attività di direzione e coordinamento ex art. 2497 bis C.C. da parte di Mazza Holding srl)

> Via T. Tasso n. 12 - 24060 Castelli Calepio (BG) ITALY VAT N° IT 01406020162 C.F. 01406020162 REG.IMPRESE DI BG - REA N. 203233 CAPITALE SOCIALE € 10.000.000 interamente versato

PTFE Products Division

Phone +39.035.4494311 Domestic Dept. Fax +39.035.4425191 Export Dept. Fax +39.035.4425238

PTFE Finished and Semifinished products http://www.guamiflon.com - info@guamiflon.com Accounting Dept. fax +39.035.4425249



